

TIG-400 P

Welder



TIG - 400P is digital DC pulse TIG models with Inverter technology, suitable for both automation application and manual welding. DC pulse function minimize the heat input for thin materials and provide a faster freezing for uphill welding.

FEATURES AND BENEFITS »

- TIG: can select HF and scratching arc starting methods, have short
- welding, long welding, spot welding and repeat welding
- Pulse: adjustable base current, peak current, pulse frequency
- MMA: adjustable arc-starting current, arc force current, easy arc starting
- All parameters can be precisely adjusted in real time
- Widely used for nuclear power installation, pipe installation,
- shipbuilding, high pressure container, etc
- Suitable for stainless steel, carbon steel, copper, titanium welding
-

PROCESSES »

DCTIG/MMA
/DC Pulsed TIG

STANDARD EQUIPMENTS »

- Power source 400 Amps - 1 unit
- Argon Regulator - 1 unit
- Air cooled WP-26 4 Meter - 1 Unit
- Earth Clamp Set - 3 Meter - 1 Unit
- Gas Hose- 2 meter - 1 Unit
-
-
-
-

TECHNICAL SPECIFICATION

Model		TIG - 400P
Rated input voltage/frequency		3 phase, 415V±10%, 50Hz
(Hz) Rated input capacity (KVA)		17.8
Rated input current (A)		25
Duty cycle (40C)		60%@400A
OCV(V)		71
MMA	Output current (A)	5-400
	Arc force (A)	10-200
TIG	Hot start (A)	20-160
	Output current (A)	5-400
	Pre-gas /post gas (s)	0.1-9.99/0.1-60
	Initial /final current (A)	10-160 /5-400
	Up-slope /down-slope (s)	0.1-10 /0.1-15
	Peak current (A)	5-400
	Base current (A)	5-400
	Pulse frequency (Hz)	0.2-20
	Pulse duty cycle	15%-85%
	Trigger mode	2/4T
	Arc ignition method	HF
Protection class		IP21S
Insulation class		H
Dimension (mm)		540*275*510
Weight (kg /lb)		31/68.34